




smart
vision lights

SW75 Brick Light SPOT LIGHT WASHDOWN

P R O D U C T D A T A S H E E T



Warranty

10
YEAR

Compliant

IEC
62471

Compliant

CE
RoHS

Rated

IP
68

Connector

5-PIN
M12

PRODUCT HIGHLIGHTS

- ✓ IP68 standards
- ✓ Stainless-steel 316 housing, silicone gasket, acrylic and polycarb
- ✓ Built-in driver
- ✓ PNP and NPN trigger signal input
- ✓ Perfect for food manufacturing and washdown environments




PRODUCT INTRODUCTION

The SW75 Brick Light spot light features a spot light that features a stainless-steel IP68 rated enclosure specially designed for food industry and washdown environments where water and harsh detergents are present. NPN or PNP trigger signals can be used to control the pulse of the light. Intensity of the light can be controlled via 1–10VDC analog signal line or by adjusting the built-in manual potentiometer.

PRODUCT SPECIFICATIONS

Electrical Input	24VDC +/-5%
Input Current	Max. 375 mA
Wattage	Max. 9.0 W
On/Off Input	PNP : +4VDC or greater to activate NPN : GND (<1VDC) to activate
PNP Line	4 mA @ 4VDC 10 mA @ 12VDC 20 mA @ 24VDC
NPN Line	15 mA @ ground (0VDC)
Yellow Indicator LED	LED strobe indicator ON = light active
Green Indicator LED	ON = power
Continuous Mode	NPN can be tied to ground OR PNP can be tied to 24VDC (not both).
Potentiometer	270° turn pot — intensity control of 10%–100%. Turn clockwise to increases intensity.
Analog Intensity	The output is adjustable from 10%–100% of brightness by a 1–10VDC signal. (Jumpering pin 5 to pin 1 will provide maximum intensity.)
Connection	5-pin M12 connector
Ambient Temperature	-18°–40°C (0°–104°F)
IP Rating	IP68
Weight	~155 g
Compliances	CE, RoHS, IEC 62471
Warranty	UV LEDs have a 2 year warranty, all other LEDs have a 10 year warranty. For complete warranty information, visit smartvisionlights.com/warranty .

WIRING CONFIGURATION



Pin	Function	Signal	Wire Color
1	Power In	+24VDC	BROWN
2	NPN	Sinking Signal	WHITE
3	GND	Ground	BLUE
4	PNP	Sourcing Signal	BLACK
5	Intensity Control	1–10VDC	GREY*

OPTIONAL
 For maximum intensity, connect pin 5 to pin 1 at +24VDC. Potentiometer intensity needs to be set to 100%.

* Some cables use green/yellow for pin 5
 For maximum intensity, tie pin 5 to pin 1 at +24VDC.
 For continuous mode: Tie PNP (pin 4) can be tied to +24VDC (pin 1) or tie NPN (pin 2) can be tied to Ground (pin 3).



RESOURCE CORNER


Additional resources, including CAD files, videos, and application examples, are available on our website.




LIGHT PATTERNS

Smart Vision Lights recommends that the SW75 be used at a working distance between 300 mm and 4000 mm.


Beam Diameter (White Light)—5700K



Beam Diameter (White Light)—5700K



Beam Diameter (White Light)—5700K



LIGHTING PATTERN FOR THE SW75 with Narrow (Standard) Lenses

Working Distance mm (inches)	Pattern (80%–100% measured intensity) mm (inches)
500 mm (19.7")	120 mm (~4.7") D
1000 mm (39.4")	240 mm (~9.4") D
2000 mm (78.8")	480 mm (~18.9") D

Typical Output Performance	Illuminance (Lux)
Distance = 500 mm	7250
<i>Illuminance measurement taken on White Lights—5700K</i>	

LIGHTING PATTERN FOR THE SW75 with Wide (W) Lenses

Working Distance mm (inches)	Pattern (80%–100% measured intensity) mm (inches)
500 mm (19.7")	180 mm (~7") D
1000 mm (39.4")	360 mm (~14.2") D
2000 mm (78.8")	720 mm (~28.3") D

Typical Output Performance	Illuminance (Lux)
Distance = 500 mm	6500
<i>Illuminance measurement taken on White Lights—5700K</i>	




LIGHTING PATTERN FOR THE SW75 with Line (L) Lenses

Working Distance mm (inches)	Pattern (80%–100% measured intensity) mm (inches)
500 mm (19.7")	100 mm (~3.9") H x 200 mm (~7.8") V
1000 mm (39.4")	200 mm (~7.8") H x 400 mm (~15.7") V
2000 mm (78.8")	400 mm (~15.7") H x 800 mm (~31.5") V

Typical Output Performance	Illuminance (Lux)
Distance = 500 mm	9800
<i>Illuminance measurement taken on White Lights—5700K</i>	


The SW75 Brick Light produces a uniform light pattern.

Working distance = 500 mm Grid set to 25 mm x 25 mm




PRODUCT DRAWING

CAD files available on our website.
Dimensions are in mm.



ILLUMINATION

SW75 Series of Brick Lights works best for:



EYE SAFETY

According to IEC 6247: 2006. Full documentation available upon request.



Notice

Exempt Group: No photobiological hazard to eyes or skin even for continuous, unrestricted use. Applicable for wavelengths 625, 850, 940, 1050, 1200, 1300, 1450, and 1550.

Caution

Risk Group 1: Possibly hazardous optical radiation emitted from this product. Do not stare at operating lamp. May be harmful to eyes. Safe for most applications except for prolonged exposure. Applicable for wavelengths 470, 505, 530, and WHI.



PART NUMBER

SW75 – [] [] [] [] – []

COLOR:



LENS:

Leave blank for Standard (Narrow)

W = Wide

L = Line

Part Number Examples:

SW75-625 SW75, 625 nm Red Wavelength, Standard (Narrow) Lens

SW75-WHI-L SW75, White, Line Lens



This light is available in our SWIR LEDs.



Additional wavelengths options available upon request.



LENS OPTICS

NARROW (STANDARD)

Narrow, 10° angle-cone lenses are standard. Standard lenses project a narrow beam of illumination and are used for long working distances.


WIDE

Wide, 25° angle-cone lenses project a large area of illumination. They create a floodlight effect, can be used for short working distances.

LINE

Line, with a 10° width and a 50° fan-angle projects a thin, narrow beam of illumination.

Additional lens options available upon request.





ACCESSORIES

Power Cables



Length	Part Number
5 m	5PM12-5
10 m	5PM12-10
15 m	5PM12-15

Power Cables (Washdown)



Length	Part Number
15 m	W5PM12-15

Washdown cable has a 316 Stainless-steel connector.



GLOSSARY

This glossary covers all Smart Vision Lights product families; some content in this section may not apply to this specific light.

TERMINOLOGY

OverDrive™ Light includes an integrated high-current strobe driver for complete LED light control.

Continuous Operation Light stays on continuously.

Multi-Drive™ Combines continuous operation and OverDrive™ strobe (high-current strobe operation) modes into one easy-to-use light.


Built-In Driver The built-in driver allows full function without the need for an external driver.

Camera to Light Connect the light directly to the camera, without the need for additional controllers or equipment.


Polarizers Filters that reduce reflections on specular surfaces.

Diffuser Used to widen the angle of light emission, reduce reflections, and increase uniformity.


TYPES OF ILLUMINATIONS



Projector




Dark Field




Radial




Bright Field




Direct




Axial



Line




Diffuse Panel



Backlight

COLOR/WAVELENGTHS LEGEND

Wavelength options range from 365 nm to 1550 nm. Additional wavelengths available for many light families.



See Part Number section for **this light's** available standard wavelengths.



Shortwave infrared LEDs are available in 1050 nm, 1200 nm, 1300 nm, 1450 nm, and 1550 nm.

Check Part Number section to see if **this light** is available in SWIR wavelengths.