





HAWK MV-4000 Safety Warnings and Symbols Key

Before using the HAWK MV-4000 Smart Camera, you should be aware of the meanings of the safety warnings and symbols on the device. The following is a list of HAWK MV-4000 symbols and their meanings.

Symbol ^a	Description
	<ul style="list-style-type: none"> • Caution: Read the <i>HAWK MV-4000 Smart Camera Guide</i>^b before using the device. The guide contains product specifications, hardware configurations, connector and cable pin assignments, wiring instructions, accessory configuration instructions, and additional information related to the operation of the device. • This product must be used as specified. The protection provided by its components may be compromised if the product is used improperly. • Refer to the electrical specifications section in the <i>HAWK MV-4000 Smart Camera Guide</i> for voltage and current ratings. • There are no user-serviceable parts inside this product. Contact Omron Microscan for repair or replacement. • To maintain IP67 conformity, all unused connectors on the HAWK MV-4000 must be capped and the optional IP case must be screwed firmly into place. • This product meets Category 1 installation requirements per industry standards. • This product is designed for use in a Pollution Degree 2 environment per industry standards^c. • This product is designed for indoor use only. • This product is designed for operation at temperatures ranging from 0° C to 50° C. • This product is not intended for use at altitudes exceeding 2000 meters.
	<ul style="list-style-type: none"> • DC current only. • The HAWK MV-4000 can only be powered using a 24VDC power source.

a. Symbol color or shape may be slightly different on the product.

b. *HAWK MV-4000 Smart Camera Guide* available on Tools Drive (P/N 37-000010-01) or at www.microscan.com.

c. Per CAN/CSA-C22.2 No 61010-1-12, UL std. No 61010-1 (3rd edition), and EN Std. No. 61010-1 (3rd edition).